MERCEDES-BENZ (EU) R-CLASS W251 R 350 251.056/156 (2009-2010)



ENGINE M272.967 Capacity: 8 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol 5W-50

DIFFERENTIAL REAR Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Change every 50000 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
Change every 25000 km	

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1 Capacity: 9 liter (Dry fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months		

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1 Capacity: 9 liter (Dry fill)		
USE	CLIMATE	
First change only	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 60000 km	·	

MERCEDES-BENZ (EU) R-CLASS W251 R 350 251.056/156 (2009-2010)



HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	

ELECTRO-HYDRAULIC POWER STEERING (EHPS) Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

POWER STEERING Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

COOLING SYSTEM Capacity: 0-0 liter (Between min an	d max.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant SP 12 EVO		
Change every 250000 km/ 180 mod	nths		

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 970 grams, Capacity: 1220 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.