

MERCEDES-BENZ (EU) R-CLASS W251 R

500 4MATIC 251.072/172 (2007-2010)



ENGINE M273.963
Capacity: 9 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

DIFFERENTIAL FRONT
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

DIFFERENTIAL REAR
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

TRANSFERBOX
Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1
Capacity: 9 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 125000 km/ 60 months

MERCEDES-BENZ (EU) R-CLASS W251 R

500 4MATIC 251.072/172 (2007-2010)


TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1

Capacity: 9 liter (Dry fill)

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 km

HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

POWER STEERING

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

COOLING SYSTEM

Capacity: 10,1-13 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 970 grams, Capacity: 1220 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.