

MERCEDES-BENZ (EU) S-CLASS W220 / V220 S 280 220.063/163 (1999-2005)

**ENGINE M112.922**

Capacity: 8 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol 5W-50

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B.

DIFFERENTIAL REAR

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B.

TRANSMISSION AUTOMATIC 722.617 5/1

Capacity: 7,5-8 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B.

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Change every 60000 km

MERCEDES-BENZ (EU) S-CLASS W220 / V220 S 280 220.063/163 (1999-2005)



ACTIVE BODY CONTROL SYSTEM

Capacity: 4 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B.

HYDRAULIC BRAKE SYSTEM

Capacity: 0,7-0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Change every 24 months

POWER STEERING

Capacity: 1 liter, Capacity: 1,25 liter (With Active Body Control system (ABC))

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B.

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >22000 km ago: Service B. Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

MERCEDES-BENZ (EU) S-CLASS W220 / V220 S 280 220.063/163 (1999-2005)



AIRCONDITIONING SYSTEM

Capacity: 950 grams, Capacity: 1050 grams (+ rear airconditioning)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.