

MERCEDES-BENZ (EU) SL-CLASS R129 SL 600 (1993-2001)



ENGINE M120
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Emperol 10W-40

PRODUCT RECOMMENDATION 3

Bi-Turbo 15W-40

Change every 15000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube LS 80W-90

Check every 30000 km

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

Check every 30000 km

MERCEDES-BENZ (EU) SL-CLASS R129 SL 600 (1993-2001)



TRANSMISSION AUTOMATIC 722.3xx 4/1
Capacity: 7,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF Dexron II-D

Check every 30000 km, change every 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF Almirol

Change every 30000 km

TRANSMISSION AUTOMATIC 722.6xx 5/1
Capacity: 8,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 30000 km

HYDRAULIC LEVELLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

Check every 30000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

MERCEDES-BENZ (EU) SL-CLASS R129 SL 600 (1993-2001)

**POWER STEERING**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

*Check every 30000 km***GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

*Check every 30000 km***COOLING SYSTEM**

Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.