

# MERCURY GRAND MARQUIS GRAND MARQUIS 4.6 V8 (1990-1997)

**ENGINE**

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 1 months, change every 5000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Check every 1 months, change every 3000 miles/ 3 months***DIFFERENTIAL REAR**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 50000 miles***DIFFERENTIAL REAR LIMITED SLIP Trac-Lok**

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 50000 miles*

# MERCURY GRAND MARQUIS GRAND MARQUIS 4.6 V8 (1990-1997)



## TRANSMISSION AUTOMATIC 4R70W 4/1

Capacity: 13,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Change every 30000 miles*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Change every 21000 miles*

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 12 months*

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>	<b>ATF-F (Ford)</b>

*Check every 6 months*

# MERCURY GRAND MARQUIS GRAND MARQUIS 4.6 V8 (1990-1997)

**COOLING SYSTEM**

Capacity: 13,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 18</b>		

*Check every 15000 miles, change every 30000 miles/ 36 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 18</b>		

*Check every 15000 miles, change every 50000 miles/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*