

MERCURY MILAN MILAN 2.5 HYBRID AWD (2010-2011)



ENGINE Atkinson 2.5
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Change every 10000 miles/ 12 months

DIFFERENTIAL REAR
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

TRANSFERBOX
Capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

TRANSMISSION CVT
Capacity: 5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

MERCURY MILAN MILAN 2.5 HYBRID AWD

(2010-2011)

**COOLING SYSTEM**

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

Change every 50000 miles/ 36 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	

*Change every 100000 miles/ 72 months***COOLING SYSTEM ELECTRONICS**

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 50000 miles/ 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 100000 miles/ 72 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.