

MERCURY MOUNTAINEER MOUNTAINEER

4.0 V6 (1998-2001)

**ENGINE**

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30	Asyntho 5W-30

Check every 1 months, change every 5000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Duranza LSP 5W-30	Asyntho 5W-30

*Check every 1 months, change every 3000 miles/ 3 months***DIFFERENTIAL REAR**

Capacity: 2,9-3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Change every 100000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

*Change every 50000 miles***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 2,9-3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

Change every 100000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

Change every 50000 miles

MERCURY MOUNTAINEER MOUNTAINEER

4.0 V6 (1998-2001)



TRANSMISSION AUTOMATIC 5R55E 5/1

Capacity: 9,5 liter (Dry fill)

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 15000 miles, change every 30000 miles

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 15000 miles, change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

PRODUCT RECOMMENDATION 3

ATF Dexron II-D

Check every 6 months

COOLING SYSTEM

Capacity: 15,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 18

Check every 15000 miles/ 6 months, change every 45000 miles

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.