MG MG-ZS MG-ZS 1.8 16V (2001-2005)



ENGINE 18K4 Capacity: 4,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	

Change every 25000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Change every 25000 km/ 12 months

TRANSAXLE AUTOMATIC CVT + StepTronic 6/1 Capacity: 4,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4016		

Check every 25000 km/ 12 months, change every 50000 km/ 48 months

TRANSAXLE MANUAL PG1 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
01 1 050001 / 10 11	4750001 /04 //	

Check every 25000 km/ 12 months, change every 175000 km/ 84 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 25000 km/ 12 months, ch	ange every 24 months	

MG MG-ZS MG-ZS 1.8 16V (2001-2005)



POWER STEERING Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 25000 km/ 12 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3
Check every 25000 km/ 12 months	,	,

COOLING SYSTEM Capacity: 4,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Check every 25000 km/ 12 months, change every 24 months		

AIRCONDITIONING

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR Capacity: 140 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.