## **MINI (EU) MINI R56 MINI COOPER S** (2006-2010)



| ENGINE N14B16<br>Capacity: 4,2 liter |                          |                          |
|--------------------------------------|--------------------------|--------------------------|
| USE                                  |                          | CLIMATE                  |
| Flexible (max)                       |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 0W-30                 | Helar SP LL-03 5W-30     | Presteza MSP 5W-30       |

| TRANSAXLE AUTOMATIC GA6F21AW (Aisin) 6/1<br>Capacity: 6 liter (Dry fill), Capacity: 4,5 liter (Service fill) |  |          |  |  |
|--|--|----------|--|--|
| USE  |  | CLIMATE  |  |  |
| Normal   |  | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   |  |          |  |  |
| SP Matic 4026  |  |          |  |  |

| TRANSAXLE MANUAL GS6-53BG/DG 6/1<br>Capacity: 1,9 liter |  |                     |  |  |
|---|--|---------------------|--|--|
| use<br>Normal   |  | climate<br>Moderate |  |  |
| PRODUCT RECOMMENDATION 1 SP Gear 5015                   |  |                     |  |  |

| HYDRAULIC BRAKE/CLUTCH SYSTEM DSC |          |  |
|-----------------------------------|----------|--|
| USE                               | CLIMATE  |  |
| Normal                            | Moderate |  |
| PRODUCT RECOMMENDATION 1          |          |  |
| Drauliquid-LV Super DOT 4         |          |  |

Change every 24 months

| COOLING SYSTEM<br>Capacity: 5,5 liter |          |
|---------------------------------------|----------|
| USE                                   | CLIMATE  |
| Normal                                | Moderate |
| PRODUCT RECOMMENDATION 1              |          |
| Coolant SP 11                         |          |
| Change every 48 months                |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.