

**MINI (EU) MINI R56 MINI ONE D (2010-2014)****ENGINE N47C16**

Capacity: 5,2 liter (Service fill)

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>	<b>Helar MSP+ 5W-40</b>

*Change every 24 months***TRANSAXLE AUTOMATIC GA6F21AW (Aisin) 6/1**

Capacity: 6 liter (Dry fill), Capacity: 4,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

**TRANSAXLE MANUAL GS6-53BG/DG 6/1**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

**HYDRAULIC BRAKE/CLUTCH SYSTEM DSC**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-LV Super DOT 4</b>		

*Change every 24 months***COOLING SYSTEM**

Capacity: 5,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

*Change every 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.