## MITSUBISHI (EU) COLT / MIRAGE COLT / MIRAGE 1.6 TURBO (1986-1988)



ENGINE 4G32		
Capacity: 4 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Check every 3000 km, change every 10	0000 km/ 12 months	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Check every 3000 km, change every 10	0000 km/ 12 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Change every 4800 km/ 3 months		
USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 4800 km/ 3 months		
TRANSAXLE AUTOMATIC 3/1		
Capacity: 5,8 liter		
USE No. 201		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 20000 km/24 months

## MITSUBISHI (EU) COLT / MIRAGE COLT / MIRAGE 1.6 TURBO (1986-1988)



TRANSAXLE MANUAL 4/1 Capacity: 2,3 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gearlube GL-5 80W-90			
Check every 20000 km/ 24 months, change every 80000 km/ 96 months			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071	
Check every 20000 km/24 months, chang	ge every 80000 km/ 96 months		

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 40000 km/ 48 months	·	

POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Labora Grease	Multi Purpose Grease 3			
Change every 60000 km/72 month	s			

PRODUCT RECOMMENDATION

## MITSUBISHI (EU) COLT / MIRAGE COLT / MIRAGE 1.6 TURBO (1986-1988)



COOLING SYSTEM Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 20000 km/ 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.