

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)

**ENGINE 4A92**

Capacity: 4,2 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-30

PRODUCT RECOMMENDATION 2

Avanza MSP 0W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30*Change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 10000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-30

PRODUCT RECOMMENDATION 2

Avanza MSP 0W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30*Change every 10000 km*

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)


TRANSAXLE MANUAL F5M43 5/1

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 20000 km/ 12 months, change every 100000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 20000 km/ 12 months, change every 40000 km*
HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 20000 km/ 12 months, change every 40000 km/ 24 months*
HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 20000 km/ 12 months, change every 40000 km/ 24 months*

MITSUBISHI (EU) ASX / RVR GA0 ASX / RVR 1.6 CLEARTEC (2010-2017)

**COOLING SYSTEM**

Capacity: 0,65 liter (Reserve tank), Capacity: 6 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 40000 km/ 24 months, change every 120000 km/ 72 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 40000 km/ 24 months, change every 180000 km/ 108 months

AIRCONDITIONING COMPRESSOR

Capacity: 70-90 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.