## MITSUBISHI (EU) CARISMA CARISMA 1.8 GDI (1997-1999)



<b>ENGINE</b> 4G93 Capacity: 3,8 liter, Filter capacity: 0,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 5/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Check every 15000 km/ 12 months	change every 75000 km/ 60 months	'

Check every 15000 km/ 12 months, change every 75000 km/ 60 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Change every 30000 km/24 months			

POWER STEERING

USE
Normal
PRODUCT RECOMMENDATION 1
ATF Dexron II-D

COOLING SYSTEM
Capacity: 6 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

Check every 30000 km/24 months, change every 60000 km/48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.