

MITSUBISHI (EU) COLT / MIRAGE COLT / MIRAGE 1.8 DIESEL (1986-1988)

**ENGINE 4G65**

Capacity: 5,7 liter, Filter capacity: 0,6 liter

| USE | | CLIMATE |
|--------|--|----------|
| Normal | | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Emperol 10W-40 | Bi-Turbo 15W-40 | |

Change every 5000 km/ 6 months

| USE | | CLIMATE |
|--------|--|----------|
| Severe | | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| Emperol 10W-40 | Bi-Turbo 15W-40 | |

*Change every 4800 km/ 3 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,1 liter

| USE | | CLIMATE |
|--------|--|----------|
| Normal | | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|---------------------------|
| SP Gear 1011 | SP Gear 5015 | Syngear TDL 75W-90 |

*Check every 20000 km/ 24 months, change every 80000 km/ 96 months***HYDRAULIC BRAKE SYSTEM**

| USE | | CLIMATE |
|--------|--|----------|
| Normal | | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Drauliquid DOT 3 | | |

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 0,8 liter

| USE | | CLIMATE |
|--------|--|----------|
| Normal | | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| ATF Dexron II-D | | |

MITSUBISHI (EU) COLT / MIRAGE COLT / MIRAGE 1.8 DIESEL (1986-1988)



GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE | | CLIMATE |
|--------------------------|-------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Labora Grease | Multi Purpose Grease 3 | |

Change every 60000 km/ 72 months

COOLING SYSTEM

Capacity: 6 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

Change every 20000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.