PRODUCT RECOMMENDATION

# MITSUBISHI (EU) CORDIA CORDIA 1.6 TURBO (1982-1988)

**ENGINE** 4G32T
Capacity: 3,5 liter, Filter capacity: 0,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Emperol 10W-40** | **Classic Racing Oil 15W-50** | **Bi-Turbo 15W-40** |

*Check every 3000 km, change every 10000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Asyntho 5W-30** | | |

*Check every 3000 km, change every 10000 km/ 12 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Emperol 10W-40** | **Classic Racing Oil 15W-50** | **Bi-Turbo 15W-40** |

*Change every 4800 km/ 3 months*

| USE | | CLIMATE |
|---|---|---|
| Severe | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Asyntho 5W-30** | | |

*Change every 4800 km/ 3 months*

**TRANSAXLE MANUAL** 5/1
Capacity: 2,3 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Gearlube GL-5 80W-90** | | |

*Check every 20000 km/ 24 months, change every 40000 km*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **SP Gear 5015** | **Gearlube RPC 75W-80** | **SP Gear 1071** |

*Check every 20000 km/ 24 months, change every 40000 km*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MITSUBISHI (EU) CORDIA CORDIA 1.6 TURBO (1982-1988)

## HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid DOT 3** | | |

*Change every 20000 km/ 24 months*

## POWER STEERING
Capacity: 0,9 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **ATF Dexron II-D** | | |

## GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Labora Grease** | **Multi Purpose Grease 3** | |

*Change every 60000 km*

## COOLING SYSTEM
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant -38 Organic NF** | | |

*Change every 20000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367