

# MITSUBISHI (EU) GALANT V GALANT 2.0

## (1985-1987)

**ENGINE 4G63**

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Classic Racing Oil 15W-50</b>	<b>Bi-Turbo 15W-40</b>

*Change every 10000 km/ 6 months*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Change every 10000 km/ 6 months*

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 10W-40</b>	<b>Classic Racing Oil 15W-50</b>	<b>Bi-Turbo 15W-40</b>

*Change every 4800 km/ 3 months*

USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

*Change every 4800 km/ 3 months***TRANSAXLE AUTOMATIC 3/1**

Capacity: 5,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Change every 40000 km***TRANSAXLE MANUAL 5/1**

Capacity: 2,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Syngear 75W-90</b>	<b>Gearlube GL-4 80W</b>

*Check every 20000 km/ 24 months, change every 80000 km/ 96 months*

# MITSUBISHI (EU) GALANT V GALANT 2.0

## (1985-1987)



### HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		
<i>Change every 40000 km/ 48 months</i>		

### HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

### POWER STEERING

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

### GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Labora Grease</b>	<b>Multi Purpose Grease 3</b>	
<i>Change every 60000 km/ 72 months</i>		

### COOLING SYSTEM

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		
<i>Change every 20000 km/ 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.