

MITSUBISHI (EU) LANCER CY0 LANCER 1.6 (2010-2011)

**ENGINE 4A92**

Capacity: 4,2 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 0W-30

PRODUCT RECOMMENDATION 3

Avanza MSP 0W-30*Change every 20000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 10000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 0W-30

PRODUCT RECOMMENDATION 3

Avanza MSP 0W-30*Change every 10000 km***TRANSAXLE AUTOMATIC F4A4A 4/1**

Capacity: 7,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

MITSUBISHI (EU) LANCER CY0 LANCER 1.6 (2010-2011)


TRANSAXLE MANUAL F5M43 5/1

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 20000 km/ 12 months, change every 100000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 20000 km/ 12 months, change every 40000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km/ 12 months, change every 40000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 20000 km/ 12 months, change every 40000 km/ 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

MITSUBISHI (EU) LANCER CY0 LANCER 1.6 (2010-2011)



COOLING SYSTEM

Capacity: 6 liter, Capacity: 0,65 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months, change every 120000 km/ 72 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 20000 km/ 12 months, change every 180000 km/ 108 months

AIRCONDITIONING SYSTEM

Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.