MITSUBISHI (EU) LANCER / MIRAGE **LANCER / MIRAGE 1.3 12V** (1996-2001)



ENGINE 4G13 Capacity: 3,3 liter, Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40
Change every 15000 km/ 12 months		

TRANSAXLE AUTOMATIC 4/1 Capacity: 7,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 15000 km/ 12 months,	ange every 90000 km/ 72 months

TRANSAXLE MANUAL 5/1 Capacity: 2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Check every 15000 km/ 12 months, change every 105000 km/ 84 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
Change every 7500 km/ 12 months	3	

KROON-OIL B.V. Postbus 149 7600 AC Almelo

MITSUBISHI (EU) LANCER / MIRAGE LANCER / MIRAGE 1.3 12V (1996-2001)



HYDRAULIC BRAKE/CLUTCH SYSTI	EM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
0		·

Check every 15000 km/12 months, change every 30000 km/24 months

POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	

Check every 30000 km/24 months, change every 60000 km/48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.