

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2008-2010)

**ENGINE 4B11T**

Capacity: 4 liter, Filter capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Asyntho 5W-30

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Helar 0W-40

Change every 20000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Asyntho 5W-30

Change every 10000 km

USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Helar 0W-40

*Change every 10000 km***DIFFERENTIAL REAR**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Check every 30000 km/ 24 months, change every 60000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Change every 30000 km

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2008-2010)

**TRANSAXLE MANUAL 5/1**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 15000 km/ 12 months, change every 195000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 15000 km/ 12 months, change every 90000 km***TRANSFERBOX**

Capacity: 0,49 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Check every 20000 km, change every 40000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Change every 20000 km***HYDRAULIC AWC SYSTEM**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2008-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

COOLING SYSTEM

Capacity: 7 liter, Capacity: 0,65 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 120000 km/ 72 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 180000 km/ 108 months

AIRCONDITIONING SYSTEM

Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.