

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2011-2015)

**ENGINE 4B11T**

Capacity: 4 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Asyntho 5W-30

Change every 20000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Helar 0W-40

Change every 20000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Duranza LSP 5W-30	Asyntho 5W-30

Change every 10000 km

USE	CLIMATE
Severe	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Avanza MSP 0W-30	Helar 0W-40

*Change every 10000 km***DIFFERENTIAL REAR**

Capacity: 0,55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 20000 km, change every 40000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 20000 km

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2011-2015)


TRANSAXLE SEMI-AUTOMATIC 6DCT470 Getrag 6/1

Capacity: 7,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Check every 15000 km/ 12 months, change every 105000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Check every 15000 km/ 12 months, change every 45000 km*
TRANSFERBOX

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 20000 km, change every 40000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 20000 km*
HYDRAULIC AWC SYSTEM

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

MITSUBISHI (EU) LANCER SPORTBACK

LANCER SPORTBACK RALLIART (2011-2015)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

COOLING SYSTEM

Capacity: 7 liter, Capacity: 0,65 liter (Reserve tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 120000 km/ 72 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 180000 km/ 108 months

AIRCONDITIONING SYSTEM

Capacity: 480-520 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.