

# MITSUBISHI (EU) OUTLANDER (SPORT) CU0W OUTLANDER (SPORT) 2.0 TURBO, 4WD (2003-2009)

**ENGINE 4G63T**

Capacity: 4,6 liter, Filter capacity: 0,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

PRODUCT RECOMMENDATION 2

**Bi-Turbo 15W-40***Change every 7500 km***DIFFERENTIAL REAR**

Capacity: 0,55 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Check every 15000 km/ 12 months, change every 90000 km/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

PRODUCT RECOMMENDATION 2

**Gearlube RPC 75W-80**

PRODUCT RECOMMENDATION 3

**SP Gear 1071***Check every 15000 km/ 12 months, change every 90000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2 liter, Capacity: 2,8 liter (4WD)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**SP Gear 5015**

PRODUCT RECOMMENDATION 3

**Syngear TDL 75W-90***Check every 15000 km/ 12 months, change every 45000 km/ 12 months*

# MITSUBISHI (EU) OUTLANDER (SPORT) CU0W OUTLANDER (SPORT) 2.0 TURBO, 4WD (2003-2009)

**TRANSFERBOX**

Capacity: 0,55 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Gearlube GL-5 80W-90</b> |  |          |

Check every 15000 km/ 12 months, change every 45000 km/ 12 months

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE                              |                           | CLIMATE                  |
|----------------------------------|---------------------------|--------------------------|
| Normal                           |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

Check every 15000 km/ 12 months, change every 30000 km/ 12 months

**POWER STEERING**

Capacity: 1 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF Dexron II-D</b>   |

Check every 15000 km/ 12 months

**COOLING SYSTEM**

Capacity: 7 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

Check every 30000 km/ 24 months, change every 60000 km/ 48 months

**AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.