MITSUBISHI (EU) SPACE GEAR SPACE **GEAR 2.5 TD 4WD** (1994-2000)



ENGINE 4D56 Capacity: 6,9 liter, Filter capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Bi-Turbo 15W-40	

Change every 7500 km/ 12 months

DIFFERENTIAL FRONT Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear 75W-90	Gearlube GL-4 80W
Check every 15000 km/ 12 months	change every 90000 km/ 72 months	'

DIFFERENTIAL REAR Capacity: 1,8 liter USE CLIMATE Normal Mediterranean PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90

Check every 30000 km/24 months, change every 90000 km/72 months

SP Gear 5015 Gearlube RPC 75W-80		SP Gear 1071
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Cold
USE		CLIMATE

Check every 30000 km/24 months, change every 90000 km/72 months

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 45000 km/ 36 months	

MITSUBISHI (EU) SPACE GEAR SPACE GEAR 2.5 TD 4WD (1994-2000)



TRANSFERBOX Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear 75W-90	Gearlube GL-4 80W

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

TRANSMISSION MANUAL 5/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear 75W-90	Gearlube GL-4 80W

Check every 10000 km/ 12 months, change every 75000 km/ 60 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change every 30000 km/24 months		1

POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 9 liter, Capacity: 10 liter (+ rear heater)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 60000 km/ 48 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.