MITSUBISHI (EU) TREDIA TREDIA 1.6 (1982-1988)



Normal PRODUCT RECOMMENDATION 1 Emperol 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Check every 3000 km, change every 10000 km/ 12 months USE Normal PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Cold Change every 5000 km/ 6 months USE Severe CLIMATE Cold Change every 5000 km/ 6 months Change every 5000 km/ 6 months	ENGINE 4G32 Capacity: 3,5 liter, Filter capacity: 0,5 liter		
PRODUCT RECOMMENDATION 1 Emperol 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Check every 3000 km, change every 10000 km/ 12 months USE Normal PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Climate Cold PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 Emperol 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	USE		CLIMATE
Emperol 10W-40 Check every 3000 km, change every 10000 km/ 12 months USE Normal Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 Emperol 10W-40 Change every 5000 km/ 6 months USE Severe CLIMATE PRODUCT RECOMMENDATION 2 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Cold PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40 CLIMATE Cold Change every 5000 km/ 6 months	Normal		Moderate
Check every 3000 km, change every 10000 km/ 12 months USE Normal Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 PROPOSE RECOMMENDATION 3 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Moderate PRODUCT RECOMMENDATION 2 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
USE NOrmal PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Depoil 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Normal PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 Emperol 10W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Moderate PRODUCT RECOMMENDATION 2 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Cold PRODUCT RECOMMENDATION 2 Classic Racing Oil 15W-50 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Check every 3000 km, change every 1000	0 km/ 12 months	
PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 Emperol 10W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	USE		CLIMATE
Asyntho 5W-30 Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Change every 5000 km/ 6 months USE Severe CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Normal		Cold
Check every 3000 km, change every 10000 km/ 12 months USE Severe PRODUCT RECOMMENDATION 1 Emperol 10W-40 Classic Racing Oil 15W-50 Change every 5000 km/ 6 months USE Severe CLIMATE PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Bi-Turbo 15W-40 CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	PRODUCT RECOMMENDATION 1		
Severe PRODUCT RECOMMENDATION 1 Emperol 10W-40 Classic Racing Oil 15W-50 Change every 5000 km/ 6 months USE Severe CLIMATE CLIMATE PRODUCT RECOMMENDATION 2 Bi-Turbo 15W-40 CLIMATE CLIMATE CLIMATE CLIMATE COID COID PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Asyntho 5W-30		
Severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Emperol 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Check every 3000 km, change every 1000	0 km/ 12 months	
PRODUCT RECOMMENDATION 2 Emperol 10W-40 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 2 CLIMATE Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	USE		CLIMATE
Emperol 10W-40 Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30 Classic Racing Oil 15W-50 Bi-Turbo 15W-40 Bi-Turbo 15W-40 Bi-Turbo 15W-40 CLIMATE COIMATE COIMAT	Severe		Moderate
Change every 5000 km/ 6 months USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
USE Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30 CLIMATE Cold Cold	Emperol 10W-40	Classic Racing Oil 15W-50	Bi-Turbo 15W-40
Severe Cold PRODUCT RECOMMENDATION 1 Asyntho 5W-30	Change every 5000 km/ 6 months		
PRODUCT RECOMMENDATION 1 Asyntho 5W-30	USE		CLIMATE
Asyntho 5W-30	Severe		Cold
	PRODUCT RECOMMENDATION 1		
Change every 5000 km/ 6 months	Asyntho 5W-30		
	Change every 5000 km/ 6 months		

TRANSAXLE AUTOMATIC 3/1 Capacity: 5,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 40000 km	

TRANSAXLE MANUAL 4/1 Capacity: 2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Syngear 75W-90	Gearlube GL-4 80W

MITSUBISHI (EU) TREDIA TREDIA 1.6 (1982-1988)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 20000 km/24 months		

POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	
Change every 60000 km	<u> </u>	

COOLING SYSTEM Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 20000 km/24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.