

NISSAN (EU) ALMERA ALMERA 1.8i (2002-2006)

**ENGINE QG18DE**

Capacity: 3 liter (Dry fill), Capacity: 2,9 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

*Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 7,7 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Change every 30000 km/ 24 months

USE	CLIMATE
<30.000 km/1 year	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 15000 km/ 12 months

USE	CLIMATE
>30.000 km/1 year	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Check every 24 months/ 30000 km

NISSAN (EU) ALMERA ALMERA 1.8i (2002-2006)



TRANSAXLE MANUAL RS5F70A 5/1

Capacity: 3 liter

USE		CLIMATE
<30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 15000 km/ 12 months

USE		CLIMATE
>30.000 km/1 year		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 24 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS AS OPTION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 15000 km/ 12 months

COOLING SYSTEM

Capacity: 6,6-6,7 liter, Capacity: 0,7 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 16	Coolant SP 14+	

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.