

NISSAN (EU) JUKE F15 JUKE 1.5 DCI (2010-2014)

**ENGINE K9K**

Capacity: 4,56 liter (Dry fill), Capacity: 4,4 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Meganza LSP 5W-30*Change every 30000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Meganza LSP 5W-30*Change every 15000 km/ 6 months***TRANSAXLE MANUAL RS6F94R 6/1**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Check every 12 months/ 30000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 30000 km/ 12 months, change every 60000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Change every 30000 km/ 12 months*

NISSAN (EU) JUKE F15 JUKE 1.5 DCI (2010-2014)



COOLING SYSTEM

Capacity: 6,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 16	Coolant SP 14+	

Check every 30000 km/ 12 months, change every 60000 km/ 48 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 16	Coolant SP 14+	

Check every 30000 km/ 12 months, change every 90000 km/ 60 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 450 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.