

# NISSAN (EU) NOTE E11 NOTE 1.5 DCI 90 (2010-2013)

**ENGINE K9K**

Capacity: 4,56 liter (Initial fill), Capacity: 4,4 liter (Service fill), Filter capacity: 0,2 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 20000 km/ 12 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 20000 km/ 12 months*

## USE

Severe

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 10000 km/ 6 months*

## USE

Severe

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Emperol 10W-40**

## PRODUCT RECOMMENDATION 3

**Bi-Turbo 15W-40***Change every 10000 km/ 6 months***TRANSAXLE MANUAL JR5 5/1**

Capacity: 2,5 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015****HYDRAULIC BRAKE/CLUTCH SYSTEM**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 40000 km/ 48 months*

# NISSAN (EU) NOTE E11 NOTE 1.5 DCI 90 (2010-2013)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 16</b>	<b>Coolant SP 14+</b>	

*Change every 60000 km/ 36 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 16</b>	<b>Coolant SP 14+</b>	

*Check every 40000 km/ 24 months, change every 100000 km/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.