

# NISSAN (USA / CAN) QUEST RE52 QUEST 3.5 (USA) (2015-2016)

**ENGINE VQ35DE**

Capacity: 5,3 liter (Dry fill), Capacity: 4,6 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 5000 miles/ 6 months*

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

PRODUCT RECOMMENDATION 2

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 3

**Avanza RPC 5W-30***Change every 5000 miles/ 6 months***TRANSMISSION CVT**

Capacity: 8,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4016***Check every 10000 miles/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4016***Check every 10000 miles/ 12 months, change every 60000 miles***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 20000 miles/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 10000 miles/ 12 months*

# NISSAN (USA / CAN) QUEST RE52 QUEST 3.5 (USA) (2015-2016)



## POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 11,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Change every 75000 miles/ 60 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

*Change every 105000 miles/ 84 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.