

NISSAN (USA / CAN) CUBE Z12 CUBE 1.8 (USA) (2009-2010)

**ENGINE MR18DE**

Capacity: 4,1 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Change every 7500 miles/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

*Change every 3750 miles/ 3 months***TRANSMISSION CVT**

Capacity: 7,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4016	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4016	

*Check every 12 months/ 15000 miles, change every 48 months/ 60000 miles***TRANSMISSION MANUAL**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Check every 12 months/ 15000 miles, change every 48 months/ 60000 miles

NISSAN (USA / CAN) CUBE Z12 CUBE 1.8 (USA) (2009-2010)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Check every 15000 miles/ 12 months</i>		

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Check every 15000 miles/ 12 months</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 7,1 liter (with CVT), Capacity: 6,8 liter (with manual transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
<i>Change every 30000 miles/ 24 months</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
<i>Change every 60000 miles/ 48 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.