

# NISSAN (USA / CAN) GT-R R35 GT-R (USA) (2011-2012)

**ENGINE VR38DETT**

Capacity: 5 liter, Filter capacity: 0,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Helar 0W-40***Change every 6000 miles/ 6 months***FINAL DRIVE FRONT**

Capacity: 0,65 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube Racing 75W-140***Check every 12000 miles/ 12 months, change every 18000 miles/ 18 months***FINAL DRIVE REAR**

Capacity: 1,55 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube Racing 75W-140***Check every 12000 miles/ 12 months, change every 18000 miles/ 18 months***TRANSMISSION SEMI-AUTOMATIC GR6Z30A 6/1**

Capacity: 9,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 2072***Check every 12000 miles/ 12 months, change every 18000 miles/ 18 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4***Check every 12000 miles/ 12 months, change every 24000 miles/ 24 months*

# NISSAN (USA / CAN) GT-R R35 GT-R (USA) (2011-2012)



## POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 11 liter, Capacity: 1,4 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

Change every 24000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.