NISSAN (USA / CAN) MURANO Z52 MURANO 3.5 (USA) (2015-2016)



ENGINE VQ35DE Capacity: 5,2 liter (Dry fill), Capacity	r: 4,8 liter (Service fill), Filter capacity: 0,3 li	ter
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 5000 miles/ 6 months	S	
USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Avanza RPC 5W-30
Change every 5000 miles/ 6 months	S	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	
Check every 10000 miles/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 20000 miles/24 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 10000 miles/ 12 months	

NISSAN (USA / CAN) MURANO Z52 MURANO 3.5 (USA) (2015-2016)



POWER STEERING Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
Check every 10000 miles/ 12 months	

_abora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
JSE		CLIMATE
GREASE POINTS/NIPPLES		OL WATE

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 75000 miles/ 60 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.