

# NISSAN (USA / CAN) ROGUE / ROGUE SELECT T31 ROGUE 2.5 (USA) (2007-2008)

**ENGINE QR25DE**

Capacity: 5,4 liter (Dry fill), Capacity: 4,6 liter (Service fill), Filter capacity: 0,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 2

**Armado Synth LSP Ultra 5W-30***Change every 7500 miles/ 6 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 2

**Armado Synth LSP Ultra 5W-30***Change every 3750 miles/ 3 months***DIFFERENTIAL**

Capacity: 0,55 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Check every 15000 miles/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90***Change every 30000 miles/ 24 months***TRANSMISSION CVT**

Capacity: 8,5 liter (+ cooler), Capacity: 8,3 liter (without external cooler)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4016***Check every 15000 miles/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4016***Check every 15000 miles/ 12 months, change every 60000 miles*

# NISSAN (USA / CAN) ROGUE / ROGUE SELECT T31 ROGUE 2.5 (USA) (2007-2008)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

*Check every 15000 miles/ 12 months*

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 0,75 liter (Reservoir), Capacity: 7,3 liter (Total)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

*Change every 30000 miles/ 24 months*

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Initial service          |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 14+</b>    |  |          |

*Change every 60000 miles/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.