## NISSAN (USA / CAN) SENTRA B16 SENTRA 2.0 (USA) (2012-2013)



ENGINE MR20DE Capacity: 4,4 liter (Dry fill), Capacity: 3,9 liter (Service fill), Filter capacity: 0,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30		
Change every 7500 miles/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		

Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30	
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30	

Change every 3750 miles/ 3 months

TRANSMISSION CVT Capacity: 7,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	
Check every 15000 miles/ 12 months	
LISE	CLIMATE

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	
Change every 60000 miles	- -

TRANSMISSION MANUAL Capacity: 2 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 SP Gear 5015	

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change every 30000 miles/24 months	

## NISSAN (USA / CAN) SENTRA B16 SENTRA 2.0 (USA) (2012-2013)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 15000 miles/ 12 months	

Check every 15000 miles/ 12 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 15000 miles/ 12 months	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Change every 75000 miles/ 60 months	-	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 105000 miles/ 84 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.