

NISSAN (USA / CAN) XTERRA WD22

XTERRA 3.3 (USA) 2WD (2002-2002)

**ENGINE VG33E**

Capacity: 3,8 liter (Dry fill), Capacity: 3,3 liter (Service fill), Filter capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40***Change every 7500 miles/ 6 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40***Change every 3750 miles/ 3 months***DIFFERENTIAL REAR**

Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Check every 15000 miles/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Change every 30000 miles/ 24 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 15000 miles/ 12 months*

NISSAN (USA / CAN) XTERRA WD22

XTERRA 3.3 (USA) 2WD (2002-2002)



TRANSMISSION AUTOMATIC 5/1
Capacity: 8,3 liter (2WD), Capacity: 8,5 liter (4WD)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Change every 30000 miles/ 24 months

TRANSMISSION MANUAL FS5W71C
Capacity: 2,8 liter (2WD), Capacity: 5,1 liter (4WD)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90

Check every 15000 miles/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Syngear 75W-90

Change every 30000 miles/ 24 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 15000 miles/ 12 months

NISSAN (USA / CAN) XTERRA WD22

XTERRA 3.3 (USA) 2WD (2002-2002)

**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 15000 miles/ 12 months***POWER STEERING**

Capacity: 1-1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 30000 miles/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 7500 miles/ 6 months***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2**COOLING SYSTEM**

Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 30000 miles/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+*Change every 60000 miles/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products.

PRODUCT RECOMMENDATION

NISSAN (USA / CAN) XTERRA WD22 XTERRA 3.3 (USA) 2WD (2002-2002)



Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.