

OLDSMOBILE (USA / CAN) ACHIEVA

ACHIEVA 2.3 16V HO W41 (1992-1993)

**ENGINE QUAD DOHC**

Capacity: 4,3 liter, Filter capacity: 0,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 7500 miles/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 3000 miles/ 3 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 9,5 liter (Overhaul capacity), Capacity: 7 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 100000 miles*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 15000 miles***TRANSAXLE AUTOMATIC Turbo-Hydramatic 125 3/1**

Capacity: 6,6 liter (Overhaul capacity), Capacity: 3,8 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 100000 miles*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 15000 miles*

OLDSMOBILE (USA / CAN) ACHIEVA

ACHIEVA 2.3 16V HO W41 (1992-1993)



TRANSAXLE MANUAL NV T550 5/1
Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

HYDRAULIC CLUTCH SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |

POWER STEERING

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Almirol | | |

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

COOLING SYSTEM

Capacity: 9,8 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

Change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.