OLDSMOBILE (USA / CAN) SILHOUETTE SILHOUETTE 3.1 V6 (1990-1993)



ENGINE LG6 Capacity: 4,25 liter, Filter capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	
Change every 7500 miles/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
PRODUCT RECOMMENDATION 1 Asyntho 5W-30	

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 100000 miles	·
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

TRANSAXLE AUTOMATIC 4/1 Capacity: 6,6 liter (Overhaul capacity), Capacity: 3,8 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 100000 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Change every 15000 miles		

OLDSMOBILE (USA / CAN) SILHOUETTE SILHOUETTE 3.1 V6 (1990-1993)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

POWER STEERING Capacity: 0,6 liter (Complete circuit), Capacity: 0,5 liter (Steering pump)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 12 liter, Capacity: 13,5 liter (+ rear airconditioning)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Change avery 20000 miles/24 menths	·	

Change every 30000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.