

OPEL ADAM M13 ADAM 1.4 (64 KW) (2013-2015)

**ENGINE** A14XEL (L2Z)

Capacity: 4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar SP LL-03 5W-30****PRODUCT RECOMMENDATION 2****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 3****Xedoz FE 5W-30***Change every 30000 km/ 12 months***TRANSAXLE MANUAL** F17 5/1

Capacity: 1,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 12 months/ 30000 km***TRANSAXLE SEMI-AUTOMATIC** F17 MTA 5/1

Capacity: 1,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081***Check every 12 months/ 30000 km***HYDRAULIC ACTUATION CLUTCH MODULE MTA****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4***Change every 24 months***HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4***Change every 24 months*

OPEL ADAM M13 ADAM 1.4 (64 KW) (2013-2015)

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.