## **OPEL AGILA B H08 AGILA B 1.0** (2008-2009)



| ENGINE K10B<br>Capacity: 2,9 liter |                          |          |  |
|------------------------------------|--------------------------|----------|--|
| USE                                |                          | CLIMATE  |  |
| Normal                             |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 |          |  |
| Presteza MSP 5W-30                 | Asyntho 5W-30            |          |  |
|                                    |                          |          |  |

Change every 15000 km/ 12 months

| TRANSAXLE MANUAL MF60B 5/<br>Capacity: 2,2 liter | 1                        |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                                     | SP Gear 5015             | Syngear TDL 75W-90       |
| Change every 45000 km/ 36 month                  | ,<br>1S                  | '                        |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal                                     |                          | Moderate |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4                  | Drauliquid-S DOT 4       |          |
|  |                          |          |

Check every 15000 km/ 12 months, change every 24 months

| COOLING SYSTEM Capacity: 4,7 liter |                          |          |
|------------------------------------|--------------------------|----------|
| USE                                |                          | CLIMATE  |
| Normal                             |                          | Moderate |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                      | Coolant SP 15+           |          |
| Check every 15000 km/ 12 months    | ·                        | ·        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.