

OPEL ASTRA G T98 ASTRA G 2.0 16V OPC (118 KW) (1999-2000)



ENGINE X20XER
Capacity: 5,25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol Racing 10W-60*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol Racing 10W-60*Change every 15000 km/ 6 months*

TRANSAXLE MANUAL F23 5/1
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90*Check every 24 months/ 30000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months*

OPEL ASTRA G T98 ASTRA G 2.0 16V OPC (118 KW) (1999-2000)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 24 months/ 30000 km

COOLING SYSTEM

Capacity: 6,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 24 months/ 30000 km

COOLING SYSTEM RED FLUID

Capacity: 6,7 liter, Capacity: 7,2 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.