## OPEL CORSA D S07 CORSA D 1.6 TURBO (110 KW) (2012-2012)



| <b>ENGINE</b> A16LEL Capacity: 4,5 liter (Dry fill) |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 5W-30                                | Presteza MSP 5W-30       | Xedoz FE 5W-30           |

Change every 30000 km/ 12 months

| TRANSAXLE MANUAL M32 6/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,2 liter (Service fill) |  |          |  |  |
|---|--|----------|--|--|
| USE   |  | CLIMATE  |  |  |
| Normal  |  | Moderate |  |  |
| PRODUCT RECOMMENDATION 1  |  |          |  |  |
| SP Gear 1081  |  |          |  |  |
| Check every 12 months/ 30000 km   |  |          |  |  |

| HYDRAULIC BRAKE/CLUTCH SYST Capacity: 0,5 liter (Dry fill) | EM ABS                   |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                                   | PRODUCT RECOMMENDATION 2 |          |
| Drauliquid-LV Super DOT 4                                  | Drauliquid-S DOT 4       |          |
|  | ·                        | ·        |

Check every 30000 km/ 12 months, change every 24 months

| COOLING SYSTEM Capacity: 5,8 liter (Dry fill) |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal  |                          | Moderate |
| PRODUCT RECOMMENDATION 1                      | PRODUCT RECOMMENDATION 2 |          |
| Coolant SP 15                                 | Coolant SP 15+           |          |
| Check every 12 months/ 30000 km               | ·                        |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.