## OPEL MOKKA J13 MOKKA 1.4 TURBO (103 KW) (2012-2014)



ENGINE A14NET (LUJ) Capacity: 4 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Xedoz FE 5W-30

Change every 30000 km/ 12 months

Check every 12 months/ 30000 km

TRANSAXLE AUTOMATIC 6T40/6T45/6 Capacity: 8-8,5 liter (Dry fill), Capacity: 4-6				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 12 months/ 30000 km				

TRANSAXLE MANUAL M32 6/1
Capacity: 1,9 liter (Dry fill), Capacity: 1,3 liter (Service fill)

USE

Normal

PRODUCT RECOMMENDATION 1

SP Gear 1081

CLIMATE

Moderate

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	·

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

PRODUCT RECOMMENDATION

## **OPEL MOKKA J13 MOKKA 1.4 TURBO (103 KW)** (2012-2014)



COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months/ 30000 km	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.