## **OPEL MONZA 22 MONZA 3.0** (1983-1987)



ENGINE 30E Capacity: 5,5 liter, Filter capacity: 0,4 liter		
USE		CLIMATE
Normal	Normal	
PRODUCT RECOMMENDATION 1		
HDX 20W-50		
Check every 500 km, change every 15000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40
Check every 500 km, change every 15000 km/ 6 months		

DIFFERENTIAL REAR Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Check every 12 months	

TRANSMISSION AUTOMATIC 3/1 Capacity: 2,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 36 months	

TRANSMISSION MANUAL 4/1 Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 12 months		

## **OPEL MONZA 22 MONZA 3.0** (1983-1987)



TRANSMISSION MANUAL Getrag 240 5/1 Capacity: 1,5 liter			
USE CLIMATE			
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Charles as an A2 magnifica	·	•	

Check every 12 months

TRANSMISSION MANUAL Getrag 265 5/1 Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube GL-4 80W		
Charles and 40 magnifica	'	·	

Check every 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
		·

Check every 500 km, change every 12 months

POWER STEERING Capacity: 1 liter		
use Normal	climate Moderate	
PRODUCT RECOMMENDATION 1	iviouerate	
ATF Dexron II-D		

COOLING SYSTEM Capacity: 10,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 500 km/ 500 hours, change	ry 24 months

## PRODUCT RECOMMENDATION

## **OPEL MONZA 22 MONZA 3.0** (1983-1987)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.