

# OPEL OMEGA A V87 OMEGA A 3000 WITH CATALYST (130 KW) (1989-1993)

**ENGINE C30NE**

Capacity: 5,5 liter, Filter capacity: 0,35 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Helar 0W-40**

## PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 3

**Emperol Racing 10W-60***Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 15000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

## PRODUCT RECOMMENDATION 1

**Helar 0W-40**

## PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

## PRODUCT RECOMMENDATION 3

**Emperol Racing 10W-60***Change every 15000 km/ 6 months***DIFFERENTIAL REAR**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 15000 km/ 12 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 15000 km/ 12 months*

# OPEL OMEGA A V87 OMEGA A 3000 WITH CATALYST (130 KW) (1989-1993)



## TRANSAXLE AUTOMATIC 4/1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

## TRANSMISSION MANUAL 5/1

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>SP Gear 5015</b>	<b>Syngear TDL 75W-90</b>

Check every 15000 km/ 12 months

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Change every 12 months

## POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

## COOLING SYSTEM

Capacity: 10,2 liter, Capacity: 11,3 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.