

OPEL OMEGA B V94 OMEGA B 2.5 TD (96 KW) (1999-2001)



ENGINE 25DT - X25DT
Capacity: 6,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Check every 500 km, change every 10000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol Racing 10W-60

Check every 500 km, change every 10000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 20000 km/ 12 months

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 20000 km/ 12 months

OPEL OMEGA B V94 OMEGA B 2.5 TD (96 KW) (1999-2001)


TRANSMISSION AUTOMATIC 4/1

Capacity: 4,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 20000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 20000 km/ 12 months, change every 110000 km/ 84 months

TRANSMISSION MANUAL 5/1

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Check every 20000 km/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 20000 km/ 12 months

OPEL OMEGA B V94 OMEGA B 2.5 TD (96 KW) (1999-2001)



COOLING SYSTEM

Capacity: 10,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 48 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.