OPEL SIGNUM Z03 SIGNUM 1.9 CDTI (88 KW) (2004-2006)



ENGINE Z19DTL Capacity: 4,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40
Change every 30000 km/ 12 months	•	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40
Change every 50000 km/24 months	1	1

TRANSAXLE MANUAL F40 6/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 30000 km/ 12 months, cha	ange every 24 months	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

OPEL SIGNUM Z03 SIGNUM 1.9 CDTI (88 KW) (2004-2006)



POWER STEERING Capacity: 0,7-1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM				
Capacity: 7 liter, Capacity: 0,5 liter (with 4 zone airconditioning system) use Normal		climate Moderate		
PRODUCT RECOMMENDATION 1 Coolant SP 15	PRODUCT RECOMMENDATION 2 Coolant SP 15+	Wioderate		
Check every 12 months/ 30000 km				
USE		CLIMATE		
Flexible (max) PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Moderate		

Check every 50000 km/24 months

Coolant SP 15

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Coolant SP 15+