

OPEL SIGNUM Z03 SIGNUM 2.2 16V DIRECT (2003-2006)



ENGINE Z22YH
Capacity: 5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Change every 30000 km/ 24 months

TRANSAXLE AUTOMATIC AF 23 5/1
Capacity: 3,5 liter (Change capacity), Capacity: 7,2 liter (Overhaul capacity)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 km/ 48 months

TRANSAXLE MANUAL F23 5/1
Capacity: 1,55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

HYDRAULIC BRAKE SYSTEM
Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

HYDRAULIC CLUTCH SYSTEM
Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

OPEL SIGNUM Z03 SIGNUM 2.2 16V DIRECT (2003-2006)



POWER STEERING

Capacity: 0,7-1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 7,6 liter (+ automatic transmission/transaxle), Capacity: 7,1 liter (+ manual transmission/transaxle), Capacity: 7,4 liter (Manual transaxle/transmission + airconditioning)

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.