

OPEL SIGNUM Z03 SIGNUM 2.8 V6 TURBO

(2007-2008)

**ENGINE Z28NET**

Capacity: 6 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Helar MSP+ 5W-40****PRODUCT RECOMMENDATION 3****Specialsynth MSP 5W-40***Change every 30000 km/ 12 months***TRANSAXLE AUTOMATIC AF 40 6/1**

Capacity: 7 liter (Initial fill), Capacity: 3 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4036***Change every 80000 km/ 72 months***TRANSAXLE MANUAL F40 6/1**

Capacity: 2,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Syngear TDL 75W-90****HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months*

OPEL SIGNUM Z03 SIGNUM 2.8 V6 TURBO

(2007-2008)



POWER STEERING

Capacity: 0,7-1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 7,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.