## **OPEL VECTRA B J96 VECTRA B 1.7 TD** (1995-1997)



<b>ENGINE</b> X17DT (TC4 EE 1) Capacity: 5,5 liter, Filter capacity: 0,35 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 20W-50			
Check every 500 km, change every 15000	km/ 12 months	· · · ·	
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60	
Check every 500 km, change every 15000	km/ 12 months		
USE		CLIMATE	
Severe		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 20W-50			
Check every 500 km, change every 15000	km/ 6 months		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar 0W-40	Emperol 5W-40	Emperol Racing 10W-60	
Check every 500 km, change every 15000	km/ 6 months		

SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
TRANSAXLE MANUAL F18 5/1 Capacity: 1,9 liter		

Check every 15000 km/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,4 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Ohennen and Ohennen (hen	:	·		

## **OPEL VECTRA B J96 VECTRA B 1.7 TD** (1995-1997)



POWER STEERING Capacity: 1,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 6,8 liter, Capacity: 6,9 liter (+ airconditioning)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 11			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.