OPEL ZAFIRA C P12 ZAFIRA C 2.0 BITURBO CDTI (143 KW) (2013-2015)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Presteza MSP 5W-30	

Change every 30000 km/ 12 months

TRANSAXLE MANUAL F40 6/1 Capacity: 1,8 liter (Dry fill), Capacity: 1,	6 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 60000 km/ 24 months	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 30000 km/ 12 months	

POWER STEERING Capacity: 0-0 liter (Between min and max.		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
Check every 12 months/ 30000 km		

OPEL ZAFIRA C P12 ZAFIRA C 2.0 BITURBO CDTI (143 KW) (2013-2015)



COOLING SYSTEM Capacity: 9 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Check every 12 months/ 30000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.