OPEL ZAFIRA C P12 ZAFIRA C 2.0 CDTI (96 KW) (2012-2015)



oderate
ИАТЕ

Change every 30000 km/ 12 months

TRANSAXLE AUTOMATIC AF 40 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Change every 80000 km/ 72 months			

TRANSAXLE MANUAL F40 6/1 Capacity: 1,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

 Change every 60000 km/ 24 months

 USE
 CLIMATE

 First change only
 Moderate

 PRODUCT RECOMMENDATION 1
 Image: Climate

Drauliquid-LV Super DOT 4	
Change every 30000 km/ 12 months	

OPEL ZAFIRA C P12 ZAFIRA C 2.0 CDTI (96 KW) (2012-2015)



POWER STEERING Capacity: 0-0 liter (Between min and max	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Charle avery 12 manths/ 20000 km	

Check every 12 months/ 30000 km

COOLING SYSTEM Capacity: 0-0 liter (Between min and m	nax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Check every 12 months/ 30000 km	· · · · ·	· · · · ·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.