PEUGEOT 306 306 1.8 (1995-1996)



ENGINE XU7JP Capacity: 4,75 liter, Filter capacity: 0,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30	

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC 4HP14 4/1 Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

TRANSAXLE MANUAL BE3/5 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube RPC 75W-80	

Check every 15000 km/ 12 months

HYDRAULIC BRAKE SYSTEM ABS AS OPTION			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 15000 km/ 12 months, change every 60000 km/ 24 months

POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 15000 km/ 12 months		

PEUGEOT 306 306 1.8 (1995-1996)



COOLING SYSTEM Capacity: 7,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 15000 km/ 12 months, change every 120000 km/ 2	24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.